

Regeneration Ovens: CR10 & CR10C

Overview

Designed specifically for the cooking/ regeneration and serving of fresh, chilled or frozen bulk food. Additional these ovens could be used for pre-chilled plated meal regeneration. Our unique multi-fan air circulation system allows fast and even heat distribution throughout.

Complete with 10 shelf positions (3 supplied), a bright, polished, stainless steel interior and satin finished hinged doors.

Operating Modes:

- Cook & Serve Use in the same manner as a traditional convection oven
- Cook Chilled Regeneration of chilled bulk food [0°C to 8°C optimum 5°C] to above 82°C
- Cook Frozen Regeneration of frozen bulk food [-6°C to -25°C optimum -18°C] to above 82°C
- Keep Hot Holding hot bulk food above 63°C, compartment controlled at 90°C

Key Features:

- Oven with Moffat's renowned, multi-fan, recirculating air system
- Temperature and count down timer display.
- Buzzer signals the end of cook cycle
- Multi-fan Technology provides a fast heat up time
- 20 min pre-heat function



Benefits:

- Compact design maximises the use of limited space
- Keep hot & boost functions

Note:

Cable & plug not provided as standard. This unit is suitable for AC supplies only. Standard terminal arrangement is for 3-phase but by linking the 3 line terminals, the unit can be connected to a single phase supply.



CR10C (Chillogen Model)

Moffat Chillogen is an innovative development from ER Moffat Ltd that combines the functions of a chilled storage unit and a regeneration oven in one convenient compartment. When used with the 24/7 timer system It provides a controlled environment for chilling storing and regenerating food automatically.

- Cook & Serve Use in the same manner as a traditional convection oven
- Rapid Chill Chill down Cooked food to below 5°C in 90min
- Keep Chilled Holding chilled bulk food below 5°C, compartment controlled between 0°C & 5°C
- Cook Chilled Regeneration of chilled bulk food [0°C to 8°C optimum 5°C] to above 82°C
- Keep Hot Holding hot bulk food above 63°C, compartment controlled at 90°C









Accessories: 24/7 program timer	Weight (kg)	Capacity	Grid Shelves	Power Rating (kw)
Food probe & HACCP compliant data recording system	130	10-1/1 GN	10 (3 Supplied)	3.7kw: 16 amp 3PH or 32 amp 1PH 5.7kw: 16 amp 3PH or 32 amp 1PH

Additional grid shelves

and temperature display

Food probe with pass/fail indicator

- Spare internal racks
- Transport loading trolleys
- Support Stands

















