Regeneration Ovens: CR5 & CR5C

Overview

Designed specifically for the cooking/regeneration and serving of fresh, chilled or frozen bulk food. Additional these ovens could be used for pre-chilled plated meal regeneration. Our unique multi-fan air circulation system allows fast and even heat distribution throughout.

Complete with 5 shelf positions (2 supplied), a bright, polished, stainless steel interior and satin finished hinged doors.



Operating Modes:

- Cook & Serve Use in the same manner as a traditional convection oven
- Cook Chilled Regeneration of chilled bulk food [0°C to 8°C optimum 5°C] to above 82°C
- Cook Frozen Regeneration of frozen bulk food [-6°C to -25°C optimum -18°C] to above 82°C
- Keep Hot Holding hot bulk food above 63°C, compartment controlled at 90°C

Key Features:

- Oven with Moffat's renowned, multi-fan, recirculating air system
- Temperature and count down timer display.
- Buzzer signals the end of cook cycle
- Multi-fan Technology provides a fast heat up time
- 20 min pre-heat function

Benefits:

- Complete with 2m long cable and plug, as standard
- Compact design maximises the use of limited space
- Keep hot & boost functions



CR5C (Chillogen Model)

Moffat Chillogen is an innovative development from ER Moffat Ltd that combines the functions of a chilled storage unit and a regeneration oven in one convenient compartment. When used with the 24/7 timer system It provides a controlled environment for chilling storing and regenerating food automatically.

- Cook & Serve Use in the same manner as a traditional convection oven
- Rapid Chill Chill down Cooked food to below 5°C in 90min
- Keep Chilled Holding chilled bulk food below 5°C, compartment controlled between 0°C & 5°C
- Cook Chilled Regeneration of chilled bulk food [0°C to 8°C optimum 5°C] to above 82°C
- Keep Hot Holding hot bulk food above 63°C, compartment controlled at 90°C











Accessories:

- 24/7 program timer
- Food probe & HACCP compliant data recording system
- Food probe with pass/fail indicator and temperature display
- Additional grid shelves
- Support Stands

Weight (kg)	Capacity	Grid Shelves	Power Rating (kw)
44	5-1/1 GN	5 (2 Supplied)	2.9







Bonnybridge





Find us on:





