

649

228

Service Panel

91

1486

1305

1446

Important Design Parameters

On the operators side of the Servery Counter a removable service panel is required to allow access to service heating elements etc.


The dimensions of the access aperture must be no less than 1325mm x 145mm.

Additionally access is required to manually operate the drain valve. Drain connection is via 15mm lever ball valve.

Warning

The unit must be maually filled with water. Capacity 27 litre A depth of 40mm must be maintained during opration.

[water level marker fitted to element cover]



Moffat Specification

Wet Heat

Immersion heated Bainmarie Well

Dimensions

Width - 1486mm Depth - 660mm Height - 649mm

Weight - 67kg

Power Rating

4.66kw

complete with a 2m long cord set & 32amp plug

-Materials

1.2mm 304 Grade St/ Steel Top, Supports & Well 0.7mm 430 Grade St/ Steel External Structure 0.7mm Galvanised Steel Undercarrage 6mm Tempered Glass Quartz Lamps

Installation

Counter Top Flush Fit Cut Out Dimensions 1492mm x 666mm x 25mm Counter Support Cut Out Dimensions 1468mm x 642mm

ı	ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)				ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS						
	Product	DROP-IN RANGE			Product No			article may be manufactured	MOFFAT		7
	Description	D4BM			without prior written co	without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved The Catering For					
	Material/Finish		Thickness		Desp/Date			ct 1956 as ammended by the opyright Act 1968.	The Catering Equipment Company		It
	Legacy P/N		Weight	67kg	Quote No.		Dwg No.	DIP-0	DIP-022844		sue
	Client				SO Number	N/A	Drawn By	Al	ВВ		
	Client Project	nt Project					Date	16/01	1/2019		
ı	E & R MOFFAT LTD	& R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk						1:20	Sheet	1/2	A4