





Moffat Specification

Cold contact chilled well complete with a drain valve, removable perforated base trays and a removable hinged well cover

Dimensions

Width - 846mm Depth - 661mm

Height - 940mm (Worktop 900mm) Weight - 64kg

Capacity of Well

670mm x 550mm x 200mm deep Can accommodate Two GN1/1 pans up to 150mm deep

Power Rating

0.75kw

complete with a 2m long cord set & 13amp plug

<u>Materials</u>
1.2mm 304 Grade St/ Steel Top & Supports
0.7mm 430 Grade St/ Steel Outer Structure

Installation

All swivel castors, two braked

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED) ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5							0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS				
Product	TROLLEYS			Product No		may be made, and no	No reproduction or publication of this drawing may be made, and no article may be manufactured		MOFFAT		
Description	VMCW2					without prior written con	or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved		The Catering Equipment		
Material/Finish		Thickness		Desp/Date			under the Copyright Act 1956 as ammended by the Design Copyright Act 1968.			ıı	
Legacy P/N		Weight	64kg	Quote No.		Dwg No.	VCP-0	77943	Iss	Issue	
Client				SO Number	STD	Drawn By	Al	3B		_	
Client Project				Approved By		Date	04/08	/2020	T	_	
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk						Scale	1:20	Sheet	1/2	A4	