



Moffat Specification

Cold contact chilled well complete with a drain valve, removable perforated base trays and a removable hinged well cover

Dimensions Width - 1176mm Depth - 661mm Height - 940mm (Worktop 900mm) Weight - 74kg

<u>Capacity of Well</u> 1000mm x 550mm x 200mm deep Can accommodate Three GN1/1 pans up to 150mm deep

Power Rating 0.75kw complete with a 2m long cord set & 13amp plug

Materials 1.2mm 304 Grade St/ Steel Top & Supports 0.7mm 430 Grade St/ Steel Outer Structure

<u>Installation</u> All swivel castors, two braked

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED) ALL DIMENSIONS IN ((mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS						
Product	TROLLEYS			Product No		No reproduction or may be made, and no	article may be manufactured	MOFFAT		7	
Description	VMCW3					without prior written con	or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved under the Convibing to the Stars are monged to the				
Material/Finish		Thickness		Desp/Date		under the Copyright Ac	under the Copyright Act 1956 as ammended by the			mp Equipment mpany	
Legacy P/N		Weight	74kg	Quote No.		Dwg No.	VCP-0	7960 Issue		sue	
Client				SO Number	STD	Drawn By	AE	3B			
Client Project				Approved By		Date	04/08	/2020		-	
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk						Scale	1:20	Sheet	1/2	A4	