



Moffat Specification

Cold contact chilled well complete with a drain valve, removable perforated base trays and a removable hinged well cover

_ <u>Dimensions</u> Width - 1506mm Depth - 661mm Height - 940mm (Worktop 900mm) Weight - 84kg

Capacity of Well 1330mm x 550mm x 200mm deep Can accommodate Four GN1/1 pans up to 150mm deep

Power Rating 0.75kw complete with a 2m long cord set & 13amp plug

-Materials 1.2mm 304 Grade St/ Steel Top & Supports 0.7mm 430 Grade St/ Steel Outer Structure

Installation All swivel castors, two braked

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)				ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS							
Product	TROLLEYS			Product No			No reproduction or pu may be made, and no a	rticle may be manufactured		MOFFAT	
Description	VMC				or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved						
Material/Finish		Thickness		Desp/Date			under the Copyright Act	1956 as ammended by the right Act 1968.	Company		IL
Legacy P/N		Weight	84kg	Quote No.			Dwg No.	VCP-0	77963	Issue	
Client				SO Number	STD		Drawn By	AE	3B		_
Client Project				Approved By			Date	04/08/2020		-	
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk							Scale	1:20	Sheet	1/2	A4