MOFFAT

Convection / Regeneration Oven : Models CR10L13 CR10L16 CR10L32

Overview

Designed specifically for the cooking / regeneration and serving of fresh, chilled or frozen bulk food. These ovens can also be used for pre-chilled plated meal regeneration. The unique multi-fan air circulation system allows fast and even heat distribution throughout. Designed for GN1/1 type pans, the CR10L has ten shelf positions (three grid shelves supplied as standard). The ovens have a bright, polished, stainless steel interior, satin finished outer panels, complete with a heavy duty hinged door with a positive cam action door catch. The unit is supplied with adjustable for height feet for table top sighting. These ovens can also be stacked one on top of the other and place on the optional a high stand, offering a more convenient working height and valuable storage space underneath. Alternatively the oven can be supplied mobile at low height. The CR10L can also have a CR5L oven stacked on top for full flexibility.



Table top feet option

Operating modes:

- Cook & Serve Use in the same manner as a traditional convection oven.
- Cook Chilled Regeneration of chilled bulk food [0°C to 8°C optimum 5°C] to above 82°C.
- Cook Frozen Regeneration of frozen bulk food [-6°C to -25°C optimum -18°C] to above 82°C.
- Keep Hot Holding hot bulk food above 63°C, compartment controlled at 90°C

Features:

- 1/1 GN compatible. Simple to transfer to serving equipment or load from other kitchen appliances
- Digital timer and thermostat guarantees precise time and temperature control.
- Simply rotary controls, temperature and count down timer display, with an audible buzzer indicating when food is ready.
- Multi fans deliver even heating across the entire oven chamber, ensuring no cool spots and consistent cooking results.
- Designed for bulk production, with 10 shelf capacity (shelf pitch is 71mm).
- Stackable system mobile or tabletop design with adjustable feet
- Shelving and supports are removable for easy cleaning
- Hi-Tech insulation
- Easy grip door catch with a cam action maintaining a tight seal.





Options:

- Additional grid shelves: Code:- VLS
- Support Stand: Code:- CRLHS
- Gastronorm pans

CR10L with mobile support stand CRLHS






CR10 mobile with locking castors

Electrical power options

Model	Weight (kg)	L x D x H (mm)	Electrical Supply	Power Rating (kw)	
CR10L13 CR10L16 CR10L32	125	815 x 751 x 927	2 x 13amp 16amp 3ph 32amp 1ph	3.75 3.75 3.75	

The 13amp model is supplied with two cables and 13amp plugs The 16amp and 32amp models must be hard-wired on site. A suitable plug and cable can be supplied for them at additional cost at time of order.





Oven stacking support channels

Oven Capacity: (usable space totals 147 litres)Height752 mmDepth347 mmWidth / length561mmShelf pitch71 mm












Support stand

Two CR10L Stacked / mobile









MADE IN BRITAIN

E&R Moffat Ltd. Bonnybridge FK4 2BS Scotland



www.ermoffat.co.uk +44 (0) 1324 812272 sales@ermoffat.co.uk