

Optional splash proof 13amp power sockets


Moffat Specification

Flat belt type conveyor. Sensor limit switch at the end of the conveyor Emergency-stop button at each end. Speed adjustable from 0 to 12 metres/minute Maintenance-free drum motor

Dimensions

Length - 8000mm Depth - 550mm Height - 900mm Weight - 95kg

Power Supply



When supplied as a motorized belt only the power requirements is 13amp 1PH. Optional splash proof 13amp sockets for auxiliary equipment can be fitted, each optional 13 amp socket is protected by a 13amp R.C.B.O. fitted in a splash proof M.C.B. board. Power supply requirement is made bespoke for each site and depending on how many sockets are fitted.

1.2mm 304 Grade St/ Steel Chassis Top & Supports. 0.7mm 430 Grade St Steel Ancillary Parts.

<u>Installation</u> Floor fixing adjustable for height feet.

ALL SHEET METAL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PA										AL PARTS
Product	CONVEYOR			Product No		Wmay be made, and no a	No reproduction or publication of this drawing may be made, and no article may be manufactured		MOFFAT	
Description	CVB8S *** 8 METRE STATIC BELT ***						or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved		The Catering Equipment	
Material/Finish		Thickness		Desp/Date			t 1956 as ammended by the byright Act 1968.		Company	
Legacy P/N		Weight	95kg	Quote No.		Dwg No.	VCP-088120-1		Issue	
Client				SO Number	STANDARD	Drawn By	N.Ra	ymen		
Client Project				Approved By		Date	16/02	/2021		-
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk							1:50	Sheet	1/2	A4