







Moffat Specification

Round cord type conveyor. Sensor limit switch at the end of the conveyor Emergency-stop button at each end.
Speed adjustable from 0 to 12 metres/minute
Maintenance-free drum motor

<u>Dimensions</u> Length - 3000mm Depth - 550mm Height - 920mm Weight - 70kg

_ <u>Materials</u>

1.2mm 304 Grade St/ Steel Chassis Top & Supports.
0.7mm 430 Grade St Steel Ancillary Parts.

Mobility Floor fixing adjustable for height feet

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED) ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5							0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS				
Product	CONVEYOR			Product No		No reproduction or p	No reproduction or publication of this drawing may be made, and no article may be manufactured		MOFFAT		
Description	CVC3S *** 3 METRE STATIC CORD ***						or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved				
Material/Finish		Thickness		Desp/Date			t 1956 as ammended by the pyright Act 1968.	Company		.t	
Legacy P/N		Weight	70kg	Quote No.		Dwg No.	VCP-088220-1		Iss	Issue	
Client				SO Number	STANDARD	Drawn By	N.Ra	ymen			
Client Project				Approved By		Date	16/02	/2021			
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk							1:25	Sheet	1/2	A4	