



## Refrigerated Multi Deck

## **Overview**

Chilled display units incorporating a cold well and 3 glass display shelves. The unique Moffat innovative "Polar Air Stream" system provides a constant recirculating cold air curtain completely enveloping the food displayed. Holding pre-chilled food at a safe, regulated temperature while retaining taste and freshness. Perfect for sandwiches, fruit, yoghurt and cold drinks. Self-contained units with accurate, digital control, automatic defrost, high pressure warning and automatic condensate evaporation. Utilising a highly efficient, naturally occurring, hermetically sealed, hydrocarbon gas type R290 reducing carbon footprint and energy consumption.

Use individual or as a part of a specialised Moffat servery counter.



## **Key Features:**

- With hygiene in mind all stainless-steel construction, inner panels are bright polished.
- 4 models in the range each with a chilled well and three fully adjustable glass shelves.
- Size 3, 4 & 5 have condensing unit set at 90° angle. Removes the need for unsightly vents in the front panels.
- Size 4 and 5 models have a storage space under at the operators left side.
- Digital thermostat and temperature control with automatic defrost.
- Advanced air flow design with unique polar air stream technology.
- Fully insulated efficient, eco-friendly, refrigeration. 24 hour operation.
- Maintaining the core product temperature of pre-chilled food below 5°C in ambient condition not exceeding 25°C and 60% relative humidity
- Automatic condensate water evaporation [no need to empty drip trays)
- Supplied with 2m long power cord and 13amp plug [13A 230v 50Hz]

## **Options:**

- Front roller blind codes.
   NB2:- size 2 unit, NB3:- size 3 unit, NB4:- size 4 unit, NB5:- size 5 unit.
- Lockable roller shutter models.
- · Various colours and styles of front and side panels are available, plastic coated steel, laminated wood type or Corian.
- Various designs of overhead illuminates gantries are available, curved or square type glass, open or full front. Island, Deli, or traditional kitchen pass types can all be fitted.
- · Solid tray slide or tubular tray rails fixed or fold down types.

















Model with open front & curved glass	Model with closed front & curved glass	Model front controls & curved glass	Model with lockable & front shutter	Weight (kg)	L x D x H (mm) (SA models are 1755 high)	Height to worktop	Power Rating/ Electrical supply
CRD2	CRDF2	CRDFC2	CRDSA2	115	947 x 700 x 1650	900mm	1.5kw / 13amp
CRD3	CRDF3	CRDFC3	CRDSA3	160	1275 x 700 x 1650	900mm	1.7kw / 13amp
CRD4	CRDF4	CRDFC4	CRDSA4	205	1603 x 700 x 1650	900mm	1.7kw / 13amp
CRD5	CRDF5	CRDFC5	CRDSA5	250	1931 x 700 x 1650	900mm	1.7kw / 32amp
Model with open front & square glass	Model with closed front & square glass	Model front controls & square glass	Model front controls & front shutter	Weight (kg)	L x D x H (mm) (SA model are 1755 high)	Height to worktop	Power Rating/ Electrical supply
CRDSL2	CRDSLF2	CRDSLFC2	CRDSLFC2	115	947 x 700 x 1655	900mm	1.5kw / 13amp
CRDSL3	CRDSLF3	CRDSLFC3	CRDSLFC3	160	1275 x 700 x 1655	900mm	1.7kw / 13amp
CRDSL4	CRDSLF4	CRDSLFC4	CRDSLFC4	205	1603 x 700 x 1655	900mm	1.7kw / 13amp
CRDSL5	CRDSLF5	CRDSLFC5	CRDSLFC5	250	1931 x 700 x 1655	900mm	1.7kw / 13amp

Note: The standard unit depth is 700mm, These models are also available at 800mm deep.

Additionally when integrated into a bespoke counter, the worktop depth can be made to suit specific design parameters.









Note: All size 2 models have straight through ventilation, with limitations when placed close to a wall (100mm air gap must be left for airflow to the compressor) all other models size 3, 4, and 5 have the ventilation in and out on one side, with no restrictions on the opposite side and these can be place up against a wall.











