

On the operators side of the Servery Counter a removable service panel is required to allow access to service heating elements etc. The dimensions of the access aperture must be no less than 1325mm x 145mm.

Additionally access is required to manually operate the drain valve.

The unit must be maually filled with water. Capacity 27 litre A depth of 40mm must be maintained during opration.

Moffat Specification

Wet Heat

Immersion heated Bainmarie Well

Dimensions

Width - 1486mm Depth - 660mm Height - 666mm Weight - 55kg

Power Rating

4.66kw

complete with a 2m long cord set & 32amp plug

Materials

1.2mm 304 Grade St/ Steel Top, Supports & Well 0.7mm 430 Grade St/ Steel External Structure 0.7mm Galvanised Steel Undercarrage 6mm Tempered Glass Quartz Lamps

Installation

Counter Top Flush Fit Cut Out Dimensions 1492mm x 666mm x 25mm Counter Support Cut Out Dimensions 1468mm x 642mm

ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS

Product	DROP-IN	Product No		No reproduction or p	rticle may be manufactured	MOFFAT				
Description	D4BMWI					or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved				
Material/Finish		Thickness		Desp/Date		under the Copyright Ac Design Cop	Company		ıı	
Legacy P/N		Weight	55kg	Quote No.		Dwg No.	DIP-113575		Issue	
Client		-		SO Number	N/A	Drawn By	AE	3B	_	_
Client Project	Approved By					Date	16/01	/2019	_	
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk						Scale	1:20	Sheet	1/2	A4