

Moffat Specification

Dimensions

Width - 740mm

Depth - 1308mm

Height - 1338mm

Weight - 170kg

Power Rating Options V2GR13 - 2.5 kw 13 amp 1PH

V2GR16 - 2.5 kw 16 amp 1PH

V2GR163 - 3.75 kw 16 amp 3PH

V2GR323 - 3.75 kw 32 amp 3PH

complete with a 2m long cord set & plug.

1.2mm 304 & 430 Grade St/ Steel Top & Supports.

0.7 & 1.2mm 430 Grade St Steel Ancillary Parts.

Plastic Coated Steel Front and Side panels.

1.0mm Alumminium Inner Structure.

6mm Perspex Full Front Screen.

Neo-Ceram Hot Top Area 1210mm x 590mm.

LED Illumination.

Fully Insulated Compatment.

Castors :- 2 Swivel Type With Brakes, 2 Fixed Direction.

Fully Programmably For 24/7 Operation.

Three Set Meal Programmes With

Boost, Hold, Pre heat, & Cleaning Functions.

Oven

Capacity 98lites

8off Gn1/1 Grid shelf positions @ 71mm pitch

Fridge

Capacity 98lites

8off Gn1/1 Grid shelf positions @ 71mm pitch

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)				ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR \pm 0.5mm, ANGULAR \pm 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS							
Product	Vgen 2018			Product No		may be made, a	n or publication of this drawing d no article may be manufactured	MOFFAT		7	
Description	V2GR					without prior writte	or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved The Catering E				
Material/Finish		Thickness		Desp/Date			ht Act 1956 as ammended by the n Copyright Act 1968.		Company		
Legacy P/N		Weight	170kg	Quote No.		Dwg No	. VGEN-	VGEN-005046		Issue	
Client				SO Number	N/A	Drawn B	У	BB		_	
Client Project				Approved By		Date	22/05	5/2018	•		
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk							1:20	Sheet	1/5	A4	